

ENGLISH

# **MOBIE34**

## **CARGO**



**SR SUNTOUR** 

# CONTENT

## 2K26 HIGHLIGHTS / TECHNOLOGY & FEATURES

---

<u>MOBIE34 CARGO SAFETY INSTRUCTION</u>	03
<u>SERIES INTRODUCTION</u>	04
<u>KEY SPECIFICATIONS</u>	05
<u>THRU AXLE INSTALLATION</u>	06
<u>TERMS AND SETUP</u>	07
<u>SAG AND AIR PRESSURE SETTING</u>	08
<u>REBOUND SETTING</u>	10
<u>SERVICE INTERVALS</u>	11
<u>GUIDE SERVICES</u>	12
<u>GUIDES DISCLAIMER /SAFETY</u>	12
<u>LOWER LEGS SERVICE</u>	13
<u>AIR CHAMBER SERVICE</u>	20
<u>TRAVEL CONVERSION</u>	28
<u>MAIN SPRING REPLACEMENT</u>	36
<u>CARTRIDGE REPLACEMENT</u>	41
<u>MOBIE34 SPECIFICATIONS</u>	48
<u>SOCIAL MEDIA / GLOBAL CONTACTS</u>	49

## WARNING

Carefully read, understand and follow the instructions provided in this manual, and keep it in a safe place for future reference. If you have any doubt whatsoever regarding the use or maintenance of any SR SUNTOUR product, please contact SR SUNTOUR. Failure to follow these warnings and instructions can result in product malfunction, causing an accident, severe injury or death.

## IMPORTANT SAFETY INFORMATION

- Read this manual thoroughly before using your suspension system.
- These instructions contain important information about the correct installation, service and maintenance of your suspension fork. Common mechanical knowledge may not be sufficient. Your suspension fork should be only be installed, serviced and/or maintained by a trained and qualified bicycle mechanic with specialized tools.
- Our suspension systems contain fluids and gases under extreme pressure. Never try to open any SR SUNTOUR suspension system! Pieces can be violently ejected.
- SR SUNTOUR suspension forks are designed as a single integrated system. To avoid product malfunction and an accident, use only genuine SR SUNTOUR spare parts. The use of third-party supplier spare parts also voids the warranty of your suspension system.
- Your suspension fork is not intended for jumps, aggressive downhill rides, freeride or dirt jumping if the warning sticker on your suspension system prohibits these activities. Disregarding these instructions may cause your suspension fork to fail, resulting in an accident, personal injury or death, and will void the warranty.

## WARNING

- SR SUNTOUR suspension fork is designed for use by a single rider.
- Select the correct suspension fork according to your frame's dimensions and your personal riding style. Installing a suspension for which does not match the geometry of your frame could result into a failure of the suspension fork or frame could result into a failure of the suspension fork or frame itself and will void the shocks warranty. Failure of the suspension fork or frame itself and will void the shocks warranty.
- Know the limits of your skill and experience, and never ride beyond them.
  - Read, understand and follow all owner's manuals provided with your bike and all of its components.
- Always be equipped with proper safety gear. This includes a properly fitted and fastened helmet.

## BEFORE EVERY RIDE

- Inspect your bicycle and suspension system including the handlebars, pedals, crank arms, seat post, saddle, etc. For any cracks, dents, bent or tarnished parts, Also search for any oil leaking out of your shocks. Be sure to check hidden areas on the underside of your bike. If any condition exists, consult a trained and qualified bicycle mechanic to determine the cause and make any necessary correction.
- Compress your suspension system with your body weight. If it feels too soft, make the necessary adjustments until you have reached the correct SAG value. Please also see the instruction in this manual regarding SAG.
- Make sure your brakes are properly installed/adjusted and work correctly.
- Spin the wheels. Make sure that wheels are perfectly centered and do not contact the suspension fork or brakes.
- If you are using a quick release system to fasten your wheel set, make sure that all levers and nuts are properly tightened. In case you are using a through axle system, make sure that all fixing bolts are tightened with the appropriate torque values. Strictly follow the instructions provided by the manufacturer of the quick release or through axle system.



## **MOBIE34 Cargo** **Modern Design For The E-Experience**

*Combine the stability and damping performance of a mountain bike fork, and a polished modern design, and you have MOBIE. Nearly every urban setting is seeing a steep rise in bicycling traffic- economical, environmental, and fun, these commutes only get better. The MOBIE is discreetly a powerful eBike rated urban fork. Featured with 32mm, 34mm and 36mm stanchions for control and stability, along with air and coil options. Comes in all the popular urban wheel sizes, including the new 20" & 24" versions for the newest cargo and mobility bikes. For added performance, we include direct brake mounts and a 15x100mm QLOC axle. Integrated fender and light mounts complete the package as so you can ride in any weather at any time of day. The e-Experience is enhanced mobility.*

---

<b>MODEL</b>	MOBIE34
<b>INTENDED USE</b>	ECargo
<b>TRAVEL</b>	80,100 mm
<b>WHEEL SIZE</b>	20" & 24"
<b>SPRING</b>	AIR/Spring w Preload
<b>CARTRIDGE</b>	Lo & R
<b>BOTTOM CASE</b>	MAGNESIUM
<b>AXLE TYPE</b>	15AH4-110, 15AH2, 15LH
<b>FEATURES</b>	LONG FENDER MOUNT

## KEY SPECIFICATIONS



**SUGGESTED CATEGORY:** ECargo

**TRAVEL:** 80 mm, 100 mm

**STANCHION:** Ø34MM, ALUMINUM ALLOY,  
HARD ANODIZED FINISH

**SPRING:** AIR AND COIL

**OFFSET:** 44mm

**BOTTOM CASE MATERIAL:** MAGNESIUM

**CROWN/STEERER TUBE:** C61 1.5" TAPER  
(OPTIONAL C61 straight STKM Steerer)



**MAX BRAKE ROTOR:** 180mm DIRECT  
MOUNT (203mm max)


**Ø15MM BOOST AXLE (LEVER OR TOOL TYPE)**

**FENDER MOUNT:** LONG MOUNTING  
POINTS

## THRU AXLE INSTALLATION

### 15AH4 BOLTED THRU AXLE ASSEMBLY

**Note:** Before installation, make sure to check the o-ring is correctly seated at the thread part.



1 Fully insert the axle on the drive-side.




2 Tighten the axle with a 6mm Allen wrench by the suggested tightening torque of 8-10 Nm.




3 Check the axle's thread. It must be visible.

## THRU AXLE REMOVAL




1 Loosen the axle on the drive side with a 6mm.



2 Pull out the axle.

## TERMS AND SETUP



### TOOLS NEEDED FOR THE ADJUSTMENT SETUP

- High pressure shock pump (up to 300psi)
- 27mm socket (item code ZFC160-R)
- Tape measure or caliper (for setting the SAG)
- Protective gloves and eyewear

### BEFORE ADJUSTING YOUR FORK

The following setting recommendations have to be considered as starting points. After a few rides and once you get used to your fork, you might need to adjust it again so you feel even more comfortable and secure. Adjustments also depend on your riding style and the type of bike you use.

## SAG / AIR PRESSURE SETTING

SAG refers to how much the fork compresses under the rider's body weight while in a normal riding position with gear. It can be easily measured by checking the position of the blue SAG indicator O-ring on the fork stanchion. After setting the fork to the recommended air pressure based on the rider's weight (see chart below), the O-ring will indicate how much the fork has compressed by showing its position above the fork seal.

1. Pump up to the suggested air pressure (refer to the chart below).
2. Sit on the bike with equipment (such as backpack) and ask somebody to hold the bike, stand on the pedals, and compress the fork several times. Then sit on your bike in your normal riding position.
3. Slide the SAG indicator O-ring down to the top of the dust seal.
4. Gently step off the bike without compressing the fork furthermore.
5. Check the O-ring position to see if the SAG setting is properly done.
6. In case if the SAG setting is not properly done, air pressure must be adjusted.
  - In order to increase the SAG, decrease the air pressure.
  - In order to decrease the SAG, increase the air pressure.

Repeat the above procedure until you can find the correct SAG setting.



## SAG / AIR PRESSURE SETTING

PER FORK STOCK TRAVEL	SAG MIN.-MAX. (mm)
80mm	12-24mm (15-30%)
100mm	15-30 mm (15-30%)

RIDER WEIGHT (KG)	(lbs)	RECOMMENDED AIR PRESSURE
< 55 kg	< 121 lbs	50 - 70 psi
55 - 65 kg	121 - 143 lbs	70 - 80 psi
65 - 75 kg	143 - 165 lbs	80 - 90 psi
75 - 85 kg	165 - 187 lbs	90 - 100 psi
85 - 95 kg	187 - 209 lbs	100 - 125 psi
95 < kg	209 < lbs	125+ psi
PRESSURE (FACTORY SETTING)		125 psi
MAX. PRESSURE		145 psi

### WARNING

Do **not exceed** max air pressure of 145Psi. Failure to comply with these instructions may cause serious damage to your product, injury or even death.

## REBOUND SETTING




Rebound controls the speed of the fork extension after compression. Always start the rebound setting process with the rebound knob (located bottom of the drive-side of the fork) in closed position by turning the adjuster knob all the way to the end of the clock-wise position (+).


### TO OPEN THE LOW-SPEED REBOUND

Turn the knob counter-clockwise toward the (-) to open the low-speed rebound. Each click allows the fork rebound faster per progression.

**Note:** Rebound tuning is relative to air pressure setting. Higher pressure should tune toward closed(+) setting. Lower pressure, in contrast, should set toward faster open setting (-).



For faster rebound, the counter clock-wise tuning should allow rider to stay leveled through fast and continuous bumps, causing compression to sink from mid to end of the stroke, thus increase chances of bottoming out and harsh impact and lost of traction.



For slower rebound, the clock-wise tuning should allow rider to skip over rougher terrain at slower speeds. Eliminating sharper feedback and gaining control in technical routes and jumps.

## SERVICE INTERVALS GUIDE

Service intervals guide are provided to allow our customer to keep his product running in the best way possible. Following this protocol assure customer to keep SR SUNTOUR product as good as new.

**After every ride:** Clean stanchions and dust wipers with light soapy water and wipe dry. Check the stanchion tubes for dents, scratches or other discoloration.

**Before each ride:** Check your SAG and adjust the pressure if necessary. Check the damper adjustments (compression/lockout and/or rebound)

**Every 50 hours:** Maintenance 1 (at the dealer)

**Every 100 hours or once a year:** Maintenance 2 (at the dealer, ideally before winter time in order to protect all parts from the effects of weather by proper greasing).

RECOMMENDED SERVICE ITEMS	AFTER EACH RIDE	AFTER 25 HOURS	AFTER 50 HOURS OR 6 MONTHS	AFTER 100 HOURS OR 12 MONTHS
Clean stanchion tubes and dust seals with soapy water and rinse with clear water	•			
Inspect stanchion tubes for wear	•			
Check fixing bolts and quick release for proper torque	•			
Clean fork with light soapy water and wipe dry	•			
Check air pressure and SAG		•		
Remove the quick release, check for deep marks in the fork dropouts		•		
Lower legs service			•	•
Air chamber service				•

## SERVICE GUIDES

---

All the information you need to keep your Sr Suntour product working perfectly.

### WARNING

Carefully read, understand and follow the instructions provided in this manual, and keep it in a safe place for future reference. If you have any doubt whatsoever regarding the use or maintenance of any SR SUNTOUR product, please contact SR SUNTOUR. Failure to follow these warnings and instructions can result in product malfunction, causing an accident, severe injury or death.

## IMPORTANT SAFETY INFORMATION

---

- Read this manual thoroughly before using your suspension system.
- These instructions contain important information about the correct installation, service and maintenance of your suspension fork. Common mechanical knowledge may not be sufficient. Your suspension fork should be only be installed, serviced and/or maintained by a trained and qualified bicycle mechanic with specialized tools.
- Our suspension systems contain fluids and gases under extreme pressure. Never try to open any SR SUNTOUR suspension system! Pieces can be violently ejected.
- SR SUNTOUR suspension forks are designed as a single integrated system. To avoid product malfunction and an accident, use only genuine SR SUNTOUR spare parts. The use of third-party supplier spare parts also voids the warranty of your suspension system.
- Your suspension fork is not intended for jumps, aggressive downhill rides, freeride or dirt jumping if the warning sticker on your suspension system prohibits these activities. Disregarding these instructions may cause your suspension fork to fail, resulting in an accident, personal injury or death, and will void the warranty.

### WARNING

- SR SUNTOUR suspension fork is designed for use by a single rider.
- Select the correct suspension fork according to your frame's dimensions and your personal riding style. Installing a suspension for which does not match the geometry of your frame could result into a failure of the suspension fork or frame could result into a failure of the suspension fork or frame itself and will void the shocks warranty. Failure of the suspension fork or frame itself and will void the shocks warranty.
- Know the limits of your skill and experience, and never ride beyond them.
  - Read, understand and follow all owner's manuals provided with your bike and all of its components.
- Always be equipped with proper safety gear. This includes a properly fitted and fastened helmet.

## BEFORE EVERY RIDE

---

- Inspect your bicycle and suspension system including the handlebars, pedals, crank arms, seat post, saddle, etc. For any cracks, dents, bent or tarnished parts, Also search for any oil leaking out of your shocks. Be sure to check hidden areas on the underside of your bike. If any condition exists, consult a trained and qualified bicycle mechanic to determine the cause and make any necessary correction.
- Compress your suspension system with your body weight. If it feels too soft, make the necessary adjustments until you have reached the correct SAG value. Please also see the instruction in this manual regarding SAG.
- Make sure your brakes are properly installed/adjusted and work correctly.
- Spin the wheels. Make sure that wheels are perfectly centered and do not contact the suspension fork or brakes.
- If you are using a quick release system to fasten your wheel set, make sure that all levers and nuts are properly tightened. In case you are using a through axle system, make sure that all fixing bolts are tightened with the appropriate torque values. Strictly follow the instructions provided by the manufacturer of the quick release or through axle system.

## LOWER LEGS SERVICE

### REQUIRED TOOLS & SUPPLIES:

- Ratchet wrench
- 10mm socket
- 8mm allen key
- 5mm allen key
- 3mm allen key
- Torque wrench (8-12N.m)
- Plastic mallet
- Rag or workshop towel
- Downhill tyre removal tool
- Dust seal installer 34mm (Sr Suntour fork Toolbox)
- SR SUNTOUR “Low friction” grease or suspension grease without lithium
- Brush
- lower legs service kit : FKA122-12



### **⚠ WARNING**

Do not attempt this intervention without the proper tool, you may damage your SR SUNTOUR product.

### **⚠ WARNING**

Always wear safety glasses and protective gloves during the maintenance of SR SUNTOUR products.

## LOWER LEGS SERVICE

If you have a rebound knob, start at **STEP 1**, if not, start at **STEP 3**

### STEP 1

On the damper side, pull off the rebound adjuster knob to remove it, then set it aside.



### STEP 2

Using an 8mm Allen key, turn the exposed bolt counterclockwise 2 turns to loosen it.



Use a mallet to strike the bolt 2-3 times. Check to ensure the bolt is in contact with the leg. Remove the bolt and set it aside.



## LOWER LEGS SERVICE

### STEP 3

IF you start here, follow this instruction for both side.  
Otherwise, on the air/spring side, use a 5mm allen key,  
turning it counterclockwise 3-4 turns to loosen the bolt.  
Use a mallet to strike the bolt 2-3 times. Check to  
ensure the nut is in contact with the leg.



Remove the nut and set it aside. Pull on the lower legs  
to remove them, and set them aside. Check bolt and  
washer for damage, if damaged replace.



### STEP 4A-MAINTENANCE

#### 1) FOAM RING MAINTENANCE

MOBIE34 CGO forks use foam rings. Carefully  
remove them with a pick.



Rinse the foams with isopropyl alcohol.



## LOWER LEGS SERVICE

---

Remove excess of isopropyl alcohol by pressing them.



Soak the foam rings into 20wt oil for 5-10 minutes.



## 2) DUST SEAL MAINTENANCE

---

Clean and grease the bushings as well as the dust seals using the dedicated SR SUNTOUR "Low-Friction" grease.



## LOWER LEGS SERVICE

Reinstall the foams in the forks




### STEP 4B – NEW DUST SEAL / FOAM RINGS

Hold the lower legs. Remove foam rings from both sides and discard them.



Remove the dust seals using a DH tire removal tool. If using a wrench, use caution not to damage the inside of the lowers. Repeat the process for the other side.



Use a workshop towel to clean the inner walls of the lower legs.



## LOWER LEGS SERVICE

Take the new foam rings and soak them in 15WT 100% synthetic suspension oil for 5-10 minutes.




Place the new dust seal onto the dedicated installation tool and press the seal by hand into the fork lowers.



Hold the lower legs with one hand and finish the installation by tapping the installation tool with a plastic mallet. Once you hear a change in the tapping sound, remove the tool and check that the seal edge is flush with the lower leg. If necessary, repeat the process until the seal is flush with the lower leg.



Grease the bushings and dust seals using the dedicated SR SUNTOUR "Low-Friction" grease.



## LOWER LEGS SERVICE

---

Reinstall the foams in the forks



### STEP 6

---

Clean the stanchions. Fully extend the damper cartridge and install the lower legs.



### STEP 7

---

First thread the bolt in by hand then use an 8mm Allen key to tighten the bolt to 12Nm.



Use an 8mm Allen key to tighten the bolt to 12Nm.



## LOWER LEGS SERVICE

Use a 3mm Allen key to set the rebound to fully-open (turning it counterclockwise) then close it by 1-2 turns (turning it clockwise).



Remove the Allen key and reinstall the rebound adjuster knob by pressing it into the bolt.



## AIR SIDE/SPRING SIDE

Install both the washer and bolt.  
Tighten them by hand.



Use a torque wrench with 5mm allen key socket and tighten to 8Nm.



## AIR CHAMBER SERVICE

### REQUIRED TOOLS & SUPPLIES:

- Ratchet wrench
- 27mm socket (ZFC160-R)
- Torque wrench (2-20N.m)
- Plastic mallet
- O-ring removal tool
- Air chamber oil (15W50synthetic oil)
- Rag or workshop towel
- SR SUNTOUR “Low friction” grease or suspension grease without lithium
- Brush
- High pressure pump (Shock pump)
- Air service kit : FKA121-06

#### **WARNING**

Always wear safety glasses and protective gloves during the maintenance of SR SUNTOUR products.

#### **WARNING**

Do not attempt this intervention without the proper tool, you may damage your SR SUNTOUR product.

# AIR CHAMBER SERVICE

## STEP 1

---

Remove the air cap and depressurize the air chamber.



## STEP 2

---

Use the dedicated 27mm socket and a ratchet to unscrew the air cap assembly.



Carefully remove the air cap assembly from the stanchion.



## AIR CHAMBER SERVICE

### STEP 4

Pull the top cap and the air chamber assembly out of the stanchion. You can help movement by pushing on the air shaft.



### STEP 5

Pull out the complete air cartridge




### STEP 6

Pull off the air cap from the air cartridge.



Push on the shaft, air piston will get out, some oil may flow from the air cartridge. Negative spring will appear too.



## AIR CHAMBER SERVICE

---

### STEP 7

---

Separate air piston from negative spring (no mechanical link). Put all the parts apart. With a workshop towel and isopropyl alcohol, clean the inside of the air cartridge.



### STEP 8

---

On top cap, remove both o-ring with a pick and then, clean with a workshop towel and isopropyl alcohol.



# AIR CHAMBER SERVICE

## STEP 9

Put the new o-ring on the top cap and grease them with Sr Suntour low friction grease.



## STEP 10

Clean the air piston with a workshop towel and isopropyl alcohol. Remove the leap ring from the air piston with a pick.



## STEP 11


Put the new leap ring on the air piston, this seal have an unic position, bigger diameter should head toward conic side of the piston. Grease it with Sr Suntour low friction grease.



# AIR CHAMBER SERVICE

## STEP 12

Take the negative spring assembly, clean it with isopropyl alcohol. Inspect it for any damaged or wear parts (if needed, replace them). Grease the spring, the middle bushing and the lower bushing.



## STEP 13

Put back the negative spring assembly in the air cartridge.



## STEP 14

Insert the lower parts of the air piston in the air cartridge. Then, use an allen key of an alloy shaft to push the piston all the way down in the air cartridge.





## STEP 15

---

Put the top cap in the stanchion, use a dedicated 27mm socket to tighten it at 15N.m



## STEP 16

---

Put the top cap in the stanchion, use a dedicated 27mm socket to tighten it at 15N.m





### STEP 17

---

Pressurize the air spring to 70 psi. Shake the air shaft to be sure the part is in the right place, you can feel movement and hear a “clunk” noise, this is the negative spring taking the right place.



### STEP 18

---

Please refer to the lower legs tutorial to install back the lower.

## TRAVEL CONVERSION

---

### REQUIRED TOOLS & SUPPLIES:

- 27mm socket (ZFC160-R)
- Ratchet wrench
- Torque wrench
- Air chamber oil (15W50 synthetic oil)
- SR SUNTOUR “Low-Friction” grease or suspension grease without lithium
- Brush
- Rag or workshop towel

### WARNING

Always wear safety glasses and protective gloves during the maintenance of SR SUNTOUR products.

### WARNING

Do not attempt this intervention without the proper tool, you may damage your Sr Suntour product

## TRAVEL CONVERSION

### STEP 1

Remove the air cap and depressurize the air chamber.



### STEP 2

Use the dedicated 27mm socket and a ratchet to unscrew the air cap assembly (picture 1).



# TRAVEL CONVERSION

## STEP 4

Pull the top cap and the air chamber assembly out of the stanchion. You can help movement by pushing on the air shaft.




## STEP 5

Pull out the complete air cartridge



## STEP 6

Pull off the air cap from the air cartridge. Push on the shaft, air piston will get out, some oil may flow from the air cartridge. Negative spring will appear too.



## TRAVEL CONVERSION

### STEP 7

---

Separate air piston from negative spring (no mechanical link). Put all the parts apart. With a workshop towel and isopropyl alcohol, clean the inside of the air cartridge.



### STEP 8

---

Clean the negative spring assembly with isopropyl alcohol. Separate spring parts from travel spacer (picture 2). Pull off all the parts from the shaft, you may need to turn parts while pulling to remove them. Check all the parts, if damaged, replace them.




## TRAVEL CONVERSION

---

### STEP 9

---

Take travel spacer (FEE247) and put it in place on the shaft, no spacer is 100mm, one spacer is 80mm, two spacers is 60mm of travel. Larger parts of the spacer take place against the top of the shaft.



### STEP 10

---

Assemble all the parts of the negative spring back on the shaft.



## STEP 12

Grease the spring, the middle bushing and the lower bushing.



## STEP 13

Put back the negative spring assembly in the air cartridge.



## STEP 14

Insert the lower parts of the air piston in the air cartridge. Then, use an allen key of an alloy shaft to push the piston all the way down in the air cartridge.





## STEP 15

---

Put the air cartridge in the stanchion.



Add 2CC of air chamber oil in the air cartridge.



## STEP 16

---

Grease the seal of the top cap with low friction grease. Put the top cap in the stanchion.



## TRAVEL CONVERSION

---

Use a dedicated 27mm socket to tighten it at 15N.m



## STEP 17

---

Pressurize the air spring to 70 psi. Shake the air shaft to be sure the part is in the right place, you can feel movement and hear a “clunk” noise, this is the negative spring taking the right place.



## STEP 18

---

Please refer to the lower legs tutorial to install back the lower.

# MAIN SPRING REPLACEMENT

## REQUIRED TOOLS & SUPPLIES:

- Sr Suntour Key FAA122
- Flat screwdriver
- Sr Suntour low friction grease or suspension grease without lithium
- Rag or workshop towel

### ⚠ WARNING

Do not attempt this intervention without the proper tool, you may damage your Sr Suntour product

### ⚠ WARNING

Always wear safety glasses and protective gloves during the maintenance of SR SUNTOUR products.

## STEP 1

With an Sr Suntour FAA122 key, untighten the preload cap and remove it.



# MAIN SPRING REPLACEMENT

## STEP 2

Push the negative spring shaft, main spring will be pushed out on top, grab it and pull it off.



## STEP 3

Put the upper fork upside down, negative spring shaft will slide out of the stanchion, grab it and take it off.



## STEP 4

Clean main spring and negative spring shaft with a towel and isopropyl alcohol. Check them, if parts are damaged, replace them.



# MAIN SPRING REPLACEMENT

## STEP 6

With a flat screwdriver, remove each top parts of the main spring.



## STEP 7

Now both ends part has been remove, with the flat screwdriver, push the bumper located inside the main spring.



# MAIN SPRING REPLACEMENT

## STEP 8

Pull bumper out of the main spring. Then, grease it with Sr Suntour low friction grease.



## STEP 9

Put bumper in place in the new main spring.



# MAIN SPRING REPLACEMENT

## STEP 10

Now Take both ends part of main spring, put them back in place by clipping them on the spring. Be sure that end cap is fully clip.



## STEP 11

Grease the negative shaft assembly with Sr Suntour Low friction grease, put it in place by pushing it inside the stanchion.



# MAIN SPRING REPLACEMENT

## STEP 12

Negative shaft assembly may not get out of the stanchion directly. In this case, softly hit the stanchion with your hand, this will get the shaft out.



## STEP 13

Grease the main spring with Sr Suntour Low friction grease, insert it in the fork stanchion.



## MAIN SPRING REPLACEMENT

---

### STEP 14

---

Put top cap on top of the main spring, push on it and turn clockwise to tighten it in the upper of the fork. Use the Sr Suntour FAA122 tool to tighten it completely.



### STEP 15

---

Follow instruction of the “lower legs service” parts of this document to finish.

# CARTRIDGE REPLACEMENT

## REQUIRED TOOLS & SUPPLIES:

- 27mm socket (ZFC160-R)
- Ratchet wrench
- 8mm allen key
- 5mm allen key
- 3mm allen key
- Torque wrench (8-20N.m)
- Flat screwdriver or pick
- Plastic mallet
- Rag or workshop towel
- Plastic tyre lever

### ⚠ WARNING

Do not attempt this intervention without the proper tool, you may damage your Sr Suntour product

### ⚠ WARNING

Always wear safety glasses and protective gloves during the maintenance of SR SUNTOUR products.

## STEP 1

On the damper side, pull off the rebound adjuster knob to remove it, then set it aside.



## STEP 2

Using an 8mm Allen key, turn the exposed bolt counterclockwise 2 turns to loosen it.



## CARTRIDGE REPLACEMENT 2CR

---

Use a mallet to strike the bolt 2-3 times. Check to ensure the bolt is in contact with the leg. Remove the bolt and set it aside.



## STEP 3

---

Use your thumb or a plastic tyre lever, push to lift knob and pull it out.



# CARTRIDGE REPLACEMENT 2CR

## STEP 4

---

Use the dedicated 27mm socket with ratchet to untighten the cartridge.



## STEP 6

---

Now pull and remove the cartridge from the fork.



## STEP 7

---

Put the cartridge in a vice, install it just under the top cap.



## STEP 8

---

With a pick of flat screwdriver, remove lock link.



## CARTRIDGE REPLACEMENT 2CR

---

With a pick of flat screwdriver, remove lock link.



### STEP 9

---


With a 5mm allen key, unscrew the top bolt in the top cap.



### STEP 10

---

With a plastic mallet, softly hit the top cap from bellow to remove it




# CARTRIDGE REPLACEMENT 2CR

## STEP 11

Put the new cartridge in the vice, put back the top cap.



Tighten the 5mm allen key bolt at 8N.m.



## STEP 12

Put back the lock link in place in the top cap.



## STEP 13

Put the cartridge in the stanchion



## CARTRIDGE REPLACEMENT 2CR

### STEP 14

Install the new cartridge in the right stanchion. Use dedicated 27mm socket and ratchet and tighten at 15 N.m.



Put back the lever by clipping it in open position.



### STEP 15

Make sure the damper cartridge shaft is aligned with the lower leg hole. If not, use a 3mm Allen key to center the shaft.



## CARTRIDGE REPLACEMENT 2CR

### STEP 16

First thread the bolt in by hand.



Use an 8mm Allen key to tighten the bolt to 12Nm.



### STEP 17

Use a 3mm Allen key to set the rebound to fully-open (turning it counterclockwise) then close it by 1-2 turns (turning it clockwise).



Remove the Allen key and reinstall the rebound adjuster knob by pressing it into the bolt.



# MOBIE34CGO

MODEL YEAR	MODEL NAME	MAIN SPECIFICATIONS										CROWN		STANCHION		STEERER TUBE	AXLE		BOTTOM CASE / BRAKE		
		E-Bike ready	Weight (g) w/o axle	Wheel / Max. suggested tire size	Max allowed Tire Width	Max allowed Tire O.D.	Travel (mm)	Damper	Spring	Offset (mm)	Met.	DIA (mm)	Met.	Finish	Size Material	O.L.D.	Axle	Met.	Max rotor DIA	Brake mount	Note
SF23	MOBIE34-CGO Boost DS LO 15AH2-110 24"	yes	-	24"x2.6"	68mm	640mm	80 100	LO	COIL w/ Preload adjuster	44	Al	34	STKM	Black	1.5"to1-1/8" tapered(CTS), reinforced STKM	ø15-110	15AH2-110	Mg	203mm	Post 180 Direct	with lamp mount*
SF23	MOBIE34-CGO Boost DS 15AH2-110 24"	yes	-	24"x2.6"	68mm	640mm	80 100	-	COIL w/ Preload adjuster	44	Al	34	STKM	Black	1.5"to1-1/8" tapered(CTS), reinforced STKM	ø15-110	15AH2-110	Mg	203mm	Post 180 Direct	with lamp mount*
SF22	MOBIE34-CGO Boost DS LO 15AH2-110 20"	yes	-	20"x2.6"	68mm	539mm	80 100	LO	COIL w/ Preload adjuster	44	Al	34	STKM	Black	1.5"to1-1/8" tapered(CTS), reinforced STKM	ø15-110	15AH2-110	Mg	203mm	Post 180 Direct	with lamp mount*
SF22	MOBIE34-CGO Boost DS 15AH2-110 20"	yes	-	20"x2.6"	68mm	539mm	80 100	-	COIL w/ Preload adjuster	44	Al	34	STKM	Black	1.5"to1-1/8" tapered(CTS), reinforced STKM	ø15-110	15AH2-110	Mg	203mm	Post 180 Direct	with lamp mount*

\*Front face on fork crown

## REFINED SIMPLICITY

---

SR SUNTOUR is a Japanese owned bicycle components suspension and drive train products for the widest range manufacturer, operating factories in Taiwan, China, and of people, from World Cup podiums, urban mobility to a Vietnam, with R&D and service offices collaborating kid's first bike. Our goal is to be the industry leader in value globally for the success of one of the world's most performance, reliability, durability, and serviceability prominent bicycle suspension components manufacturer. following our guiding principle REFINED SIMPLICITY. With this global infrastructure we strive to create With roots tracing back to 1912, established 1988.

## SOCIAL MEDIA / CONTACT

---



**SOCIAL MEDIA**  
CLICK TO VISIT  
SR SUNTOUR ONLINE



**CONTACT**  
CLICK TO CONTACT OUR  
WORLDWIDE DISTRIBUTORS



## SR SUNTOUR CORPORATE

---

### TAIWAN HEADQUARTER

SR SUNTOUR INC.  
#7 Hsing Yeh Rd.,  
Fu Hsing Industrial Zone, Chang Hua  
Taiwan 506027  
Tel. +886-4-7695115  
Fax. +886-4-7694028  
service@srsuntour.com.tw

### JAPAN

SR SUNTOUR JAPAN  
NR Bldg. 4F, 3-13-13  
Kuramae, Taito-ku,  
Tokyo 111-0051, Japan  
Tel. +81-(0)3-5829-9211  
Fax. +81-(0)3-5829-9241

### BELGIUM (EU)

SR SUNTOUR EUROPE S.A.  
Bld. Henri Rolin 5Bis  
1410 Waterloo Belgium  
Tel. +32-23544676  
Fax. +32-23547835  
Sales.sab@srsuntourcycling.com

### CHINA (SHEN ZHEN) SR

SUNTOUR SHEN ZHEN CO. LTD  
Suibei Industrial Zone, Suibei Rd.,  
Gongming Town, Guangming  
District, Shen Zhen, China Tel.

+86-755-27105433 Fax. +86-  
755-27105633

### CHINA (KUN SHAN) SR

SUNTOUR KUN SHAN  
CO. LTD 1500 Honghu Rd., Peng  
Lang, Kun Shan Development  
Zone, Jiang Su Province, China Tel.  
~~+86-512-5518-8088~~ Fax. ~~+86-  
512-5517-1117~~

### GERMANY (EU)

SR SUNTOUR EUROPE GMBH

Riedstrasse 31

83627 Warngau

Germany

Tel. +49-8021-50793-0

Fax. +49-8021-50793-29

service@srsuntour-cycling.com

### GERMANY (EU)

SR SUNTOUR DÜSSELDORF GMBH

Fichtenstr. 115

40233 Düsseldorf

Germany

Tel. +49-2115-42689-50

Fax. +49-2115-42347-76

### USA

SR SUNTOUR NORTH AMERICA

14511 NE 10th Avenue

Vancouver WA 98685

United States

Tel. 360-737-6450

service@srsuntourna.com

### USA

SR SUNTOUR SERVICE CENTER

910 Watson Avenue

Madison WI 53713

United States

Tel. 608-229-6610

service@usulcorp.com

### VIETNAM SR SUNTOUR

VIETNAM CO. LTD Lot. 17-8,

Street 3B, Protrade International

Tech Park, An Tay Commune, Ben

Cat Town, Binh Duong Province,

Vietnam. Tel. +84-(0)274-3721-

883 Tax Code: 3702401047

### FRANCE (EU)

SR SUNTOUR FRANCE SAS

Alpespace

604 Voie Galilée,

73800 Sainte-Hélène-Du-Lac, France

Tel. +33-4-85-86-00-99

Fax. +33-4-79-28-69-71

sav@srsuntour-cycling.com

### WWW.SRSUNTOUR.COM

Copyright © 2024 SR SUNTOUR inc. All rights reserved.  
Specifications are subject to change for improvement  
without notice.

